

# OMNIKEY® 5127CK - Mini Reader Board

## Embedded CCID and keyboard wedge RFID reader board

HID Global's OMNIKEY® 5127CK-Mini reader board opens market opportunities for system integrators seeking simple integration and development of readers using standard interfaces such as CCID, UART or Keyboard Wedge.



The 5127CK-Mini reader board complements the 5427CK reader by providing a very compact design for installation in space-constrained solutions.

The CCID interface enables integrators to design finished readers without the need to install or maintain drivers, eliminating complex software lifecycle management issues in the field and accelerating introduction of finished devices in the market.

With the Keyboard Wedge functionality, the reader can retrieve data from a card that is presented to the reader and directly input the card data into an application using keystroke emulation. This eliminates the need for customers to manually enter the card data into an application.

The OMNIKEY 5127CK-Mini reader board offers the market-proven OMNIKEY reader feature set and supports low and high frequency technology within a single device. It also supports the latest mobile access solutions via NFC or Bluetooth Smart.

Key features of the OMNIKEY 5127CK-Mini reader board include support for the most common low and high frequency card technologies, including Seos®, iCLASS, MIFARE Classic, MIFARE DESFire EV1/EV2 and HID Prox. It also includes an integrated management tool that enables field updates to readers for new firmware or changing configuration settings.

For quick and easy integration, HID Global provides an OMNIKEY 5127CK reader board Developer Tool Kit (DTK). The DTK provides the necessary tools, documentation and developer resources material to shorten integration cycles and speed time to market with finished products.



### KEY BENEFITS:

- Multi-Interface Support – CCID, Keyboard Wedge and UART interfaces offer flexible integration options for a wide range of applications.
- Dual frequency and mobile access – Simultaneously supports low and high frequency credentials, including iCLASS Seos®, HID Prox®, iCLASS SE®, MIFARE Classic® and MIFARE® DESFire® EV1 and EV2; as well as NFC and Bluetooth for mobile devices.
- Compact design – Very small footprint provides capability for installation in space-constrained designs.
- Industrial Housed Option – Rugged case providing protection in the embedded environment.

### MOBILE ENABLED READER FEATURES:

- Includes Apple's Enhanced Contactless Polling (ECP) application to support credentials in Apple Wallet
- Adjustable read settings control overall power and read range of Mobile IDs, enabling flexibility for both close-proximity "tap" and long-range "Twist and Go" distances
- Read settings administered using mobile phone during installation
- Directional antenna enables long-range reading distances up to 2m in correct orientation in front of the reader and not behind it

For further information please visit the Developer Center:

[hidglobal.com/main/developers/omnikey-5127-ck/](http://hidglobal.com/main/developers/omnikey-5127-ck/)

# OMNIKEY® 5127CK-Mini Reader Board



## CCID SUPPORT

- Native CCID implementation supporting Windows®, LINUX® and Mac® operating systems

## KEYBOARD WEDGE

- Fully configurable and programmable keyboard wedge functionality featuring an integrated management console
- Flexible configuration of data structures and output modes

## UART

- Fully featured serial protocol allowing low level integration into host applications
- Autonomous credential processing with card data sent directly over the serial interface

## BROAD CREDENTIAL SUPPORT

- NFC and Bluetooth support for Mobile devices
- Dual frequency functionality allowing support for both low and high frequency credentials simultaneously
- HID Prox®, Indala® & EM Prox, MIFARE Classic®, MIFARE® DESFire® EV1/EV2, iCLASS®, iCLASS SE®, iCLASS Seos®, HID Elite®, and other SIO enabled credentials
- Includes Apple's Enhanced Contactless Polling (ECP) application to support credentials in Apple Wallet

## ENHANCED LIFECYCLE MANAGEMENT

- Easy firmware updates and configuration setting utilizing a Web interface, SNMP messages and configuration cards
- Developer Tool Kit (DTK) available that contains product samples, development documentation, sample code and access to HID's developer portal

### 13.56 MHz HF and 125Khz LF Smart Card Reader with CCID and Keyboard Wedge Interface

Base Model Number	OMNIKEY® 5127CK-Mini	
Bluetooth functionality	WITH BLUETOOTH	WITHOUT BLUETOOTH***
<b>Dimensions</b>	Reader Board: 50 x 35 x 8.94mm (1.96" x 1.38" x 0.35") Industrial Housing: 55 x 40 x 16mm (2.2" x 1.6" x 0.63")	
<b>Weight</b>	Reader Board: 10.5g (0.4 oz) Industrial Housing: 24.4g (0.9oz)	
<b>Power Supply</b>	Bus powered	
<b>Current Requirements</b>	Base Power consumption (RF interface deactivated) - Average 60mA; HF, Prox, amd BLE activated - Average 134mA, Peak 220mA; HF polling only - Average 84mA, Peak 160mA; Prox polling only - Average 73mA, Peak 130mA; BLE advertisement only - Average 60mA, Peak 75mA	
<b>Operating Temperature</b>	-4° to 158° F (-20° to 70° C)	
<b>Operating Humidity</b>	10 - 90% Relative Humidity	
<b>Storage Temperature</b>	-4° to 176° F (-20° to 80° C)	
<b>CONTACTLESS SMART CARD INTERFACE</b>		
<b>Protocols and Cards HF*</b>	iCLASS, iCLASS SE/SR, iCLASS Seos, MIFARE Classic, MIFARE DESFire 0.6, MIFARE DESFire EV1/EV2, MIFARE Ultralight C, MIFARE Ultralight, FeliCa (Idm) CEPAS (CAN), ISO 14443A/B, ISO15693, Support for ISO18092 NFC Tag type 1, 2, 3, 4, 5, T=CL, SmartMx, Student ID in Apple Wallet	
<b>Protocols and Card LF*</b>	HID Prox, Indala Prox, EM Prox, EM4100/4102/4200/4305/4450, AWID Prox, Hitag 1.2.3, ASK, PSK, FSK	
<b>BLUETOOTH INTERFACE</b>		
<b>Supported Functions</b>	HID Global Mobile Access Service	HID Global Mobile Access Service using NFC (Android Only)
<b>HOST INTERFACE</b>		
<b>USB Interface</b>	USB 2.0 Full Speed Device (12 Mbps); USB 3.0 extended operability, tested with hubs/controllers	
<b>UART Interface</b>	Baud Rate 9600 to 921600bps; OK5127 Serial Protocol	
<b>Operating Systems</b>	Windows 10/8.1/8/7/Server 2016/Server 2012/Server 2008R2; Linux Debian 6.0+ / Ubuntu 11.04+/ Fedora 15+; Open SUSE 11.4+; Mac OS X**; Android™ 4.x to 9.x**	
<b>PC/SC Driver</b>	Compliant with native OS CCID drivers (in CCID mode) HID proprietary PC/SC drivers available for: Windows® XP / Vista™ / 7 (32 bit / 64 bit) / 8, 2003 Server, 2008 R2 Server, Linux (32 / 64 bit, incl. Debian 6.0, Fedora 15, OpenSUSE 11.4, Ubuntu 11.04) & Mac OS X (10.5 Leopard and higher, Intel 32 / 64 bit)	
<b>Keyboard Driver</b>	Native driver from operating system supporting MF-102 keyboard (Windows/Linux/Mac)	
<b>Supported APIs</b>	PC/SC - API, SAM - API	
<b>HUMAN INTERFACE</b>		
<b>Status Indicators</b>	Reader Board: Dual color LED (Green=ready, Red=busy); Industrial Housing: Buzzer (Programmable)	
<b>Connectors</b>	Micro USB connector (cable not included); Pico Blade Connector (UART Interface)	
<b>Optional Accessories</b>	Cable Management Kit	
<b>Approvals/Environmental</b>	Compliant to ROHS/REACH, WEEE, IEC 60950-1, CE, UKCA, FCC Modular, IC (Canada)	
<b>Warranty</b>	One year manufacturer's warranty	

\*For up to date credential support please refer to [Credential Support Matrix](#)

\*\* CCID and KeyBoard Wedge support

\*\*\* Available as Reader Board Only (not available with Industrial Housing)

For more information, please [click here](#).



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +353 91 506 900

Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108

For more global phone numbers [click here](#)

© 2023 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2023-08-29-eat-ok-5127ck-mini-reader-board-ds-en

PLT-02675

Part of ASSA ABLOY